

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

Supplementary Preliminary Amendment
Application S/N 10/712,328
Docket Nr. PDS-003C4 Page 2 of 10

In the claims:

Claims 1 - 127: (Cancelled)

128. (New) A power supply subsystem for providing electrical power to a local area network node over communication cabling, the power supply subsystem comprising:

a power management and control unit;

programmable current limiting circuitry responsive to said power management and control unit to provide a programmable current limited output;

voltage measurement means; and

at least one of a combiner and a power supply interface operative to couple said programmable current limited output to the communication cabling;

said power management and control unit being further operative to:

measure, utilizing said voltage measuring means at a plurality of pre-determined intervals, a voltage developed in accordance with said coupled programmable current limited output; and

determine, as a consequence of said measured voltage whether characteristics of the node allow it to receive power over the communication cabling.

129. (New) A power supply subsystem according to claim 128, wherein said voltage measuring means is operative to measure the voltage at the output of said programmable current limiting circuitry.

Supplementary Preliminary Amendment
Application S/N 10/712,328
Docket Nr. PDS-003C4 Page 3 of 10

130. (New) A power supply subsystem according to claim 128, wherein said voltage measuring means is operative to measure the voltage supplied to the communication cabling.

131. (New) A power supply subsystem according to claim 128, wherein said power management and control unit is further operable, prior to said coupling said programmable current limited output to the communication cabling, to measure, utilizing said voltage measuring means, a pre-existing voltage present across a line associated with the communication cabling.

132. (New) A power supply subsystem according to claim 131, wherein in the event that said measured pre-existing voltage exceeds a predetermined threshold, said power management and control unit is further operable to classify the line as externally voltage fed.

133. (New) A power supply subsystem according to claim 132, wherein said power management and control unit is operative to couple said programmable current limited output to the communication cabling only in the event that the line is not classified as externally voltage fed.

134. (New) A power supply subsystem according to claim 128, wherein said power management and control unit further determines the status of the local area network node for which power is to be provided as a consequence of said measured voltage, said status comprising one of a short circuit condition, a no load

Supplementary Preliminary Amendment
Application S/N 10/712,328
Docket Nr. PDS-003C4 Page 4 of 10

condition, a network interface card load condition and a power over LAN load condition.

135. (New) A power supply subsystem according to claim 134, wherein said power management and control unit is further operable to report said status to a network workstation.

136. (New) A method for supplying power to a local area network node over communication cabling, the method comprising:

injecting current-limited current into communication cabling connected to the local area network node;

measuring a voltage developed in accordance with said injected current limited current across said communication cabling at a plurality of pre-determined intervals; and

determining, as a consequence of said measured voltage at said plurality of pre-determined intervals whether characteristics of the local area network node allow it to receive power over the communication cabling.

137. (New) A method according to claim 136, wherein said measuring is accomplished at the output of a current-limited supplying circuitry, said current-limited supplying circuitry supplying said injected current-limited current.

138. (New) A method according to claim 136, wherein said measuring is accomplished across a line associated with the communication cabling.

Supplementary Preliminary Amendment
Application S/N 10/712,328
Docket Nr. PDS-003C4 Page 5 of 10

139. (New) A method according to claim 136, further comprising prior to said injecting, measuring a pre-existing voltage across a line associated with the communication cabling.

140. (New) A method according to claim 139, further comprising:

in the event said measured pre-existing voltage exceeds a predetermined threshold,

classifying the line associated with the communication cabling as externally voltage fed.

141. (New) A method according to claim 140, wherein said injecting is performed only in the event that said measured pre-existing voltage does not exceed said predetermined threshold.

142. (New) A method according to claim 136, further comprising determining a status of the local area network node for which power is to be provided over the communication cabling, said status comprising one of a short circuit condition, a no load condition, a network interface card load condition and a power over LAN load condition.

143. (New) A method according to claim 142, wherein said determining a status of the local area network node is a consequence of said measured voltage.

144. (New) A method according to claim 142, further comprising reporting said determined status to a network workstation.

Supplementary Preliminary Amendment
Application S/N 10/712,328
Docket Nr. PDS-003C4 Page 6 of 10

145. (New) A local area network providing power over communication cabling comprising:

a LAN switch;

a plurality of local area network nodes;

communication cabling enabling data communication between said

LAN switch and said plurality of local area network nodes; and

a power supply subsystem, said power supply subsystem comprising:

a power management and control unit;

programmable current limiting circuitry responsive to said power management and control unit to supply a programmable current limited output;

voltage measurement means; and

at least one of a combiner and a power supply interface operative to couple said programmable current limited output to said communication cabling,

said power management and control unit being operative to:

measure, utilizing said voltage measuring means at a plurality of pre-determined intervals, a voltage developed in accordance with said coupled programmable current limited output; and

determine, as a consequence of said measured voltage whether characteristics of at least one of said plurality of local area network nodes allow it to receive power over said

Supplementary Preliminary Amendment
Application S/N 10/712,328
Docket Nr. PDS-003C4 Page 7 of 10

communication cabling.

146. (New) A local area network according to claim 145, wherein said voltage measuring means is operative to measure the voltage at the output of said programmable current limiting circuitry.

147. (New) A local area network according to claim 145, wherein said voltage measuring means is operative to measure the voltage supplied to said communication cabling.

148. (New) A local area network according to claim 145, wherein said power management and control unit is further operable, prior to said coupling of said programmable current limited output to said communication cabling, to measure utilizing said voltage measuring means, a pre-existing voltage present across a line associated with said communication cabling.

149. (New) A local area network according to claim 148, wherein in the event that said measured pre-existing voltage exceeds a predetermined threshold, said power management and control unit is further operable to classify said line as externally voltage fed.

150. (New) A local area network according to claim 149, wherein said power management and control unit is operative to couple said programmable current limited output to said communication cabling only in the event that said line is not classified as externally voltage fed.

Supplementary Preliminary Amendment
Application S/N 10/712,328
Docket Nr. PDS-003C4 Page 8 of 10

151. (New) A local area network according to claim 145, wherein said power management and control unit further determines the status of said at least one of said plurality of local area network nodes for which power is to be provided, said status comprising one of a short circuit condition, a no load condition, a network interface card load condition and a power over LAN load condition.

152. (New) A local area network according to claim 151, wherein said determined status is a consequence of said measured voltage.

153. (New) A local area network according to claim 151, further comprising a network workstation, said power management and control unit reporting said status to said network workstation.

154. (New) A local area network according to claim 145, wherein said power supply subsystem and said LAN switch are located in a hub.

155. (New) A local area network according to claim 145, wherein said power supply subsystem is located between said LAN switch and said at least one of said plurality of local area network nodes.

156. (New) A local area network according to claim 145, wherein said power supply subsystem is located between said LAN switch and said plurality of network nodes, said communication cabling connecting said LAN switch and said plurality of network nodes via said power supply subsystem.

Supplementary Preliminary Amendment
Application S/N 10/712,328
Docket Nr. PDS-003C4 Page 9 of 10

157. (New) A power supply subsystem for providing electrical power to a local area network node over communication cabling, the power supply subsystem comprising:

- a power management and control unit;
- programmable current limiting circuitry responsive to said power management and control unit to supply a programmable current limited output;
- voltage measurement means;
- at least one of a combiner and a power supply interface operative to couple said programmable current limiting output to the communication cabling;
- said power management and control unit being operative to:

- measure, utilizing said voltage measuring means at a plurality of pre-determined intervals, a voltage developed in accordance with said coupled programmable current limited output, said voltage being measured across a line associated with the communication cabling;

- determine, as a consequence of said measured voltage at said plurality of pre-determined intervals whether characteristics of the node allow it to receive power over the communication cabling; and

- in the event that said characteristics of the node allow it to receive power over the communication cabling, provide said programmable current limited output via said at least one of a combiner and a power supply interface over the communication cabling to the node.